

R750-IR (Immersion Ready)

General purpose server optimized to address the most demanding workloads



The Dell EMC PowerEdge R750 optimized for Immersion by UNICOM Engineering, R750-IR, powered by the 3rd Generation Intel Xeon Scalable processors is the optimal rack server to address application performance and acceleration. The R750-IR is a dual-socket/2U rack server that delivers outstanding performance for the most demanding workloads. It supports 8 channels of memory per CPU, and up to 32 DDR4 DIMMs @ 3200 MT/s speeds. In addition, to address substantial throughput improvements the R750-IR supports PCle Gen 4 and up to 24 SSD drives with liquid immersion cooling features to support increasing power and thermal requirements. This makes the R750-IR an ideal server for data center standardization on a wide range of workloads including Database and Analytics, High-performance computing (HPC), Traditional corporate IT, Virtual Desktop Infrastructure, and Al/ML environments that require performance, extensive storage and GPU support.

Gain a Competitive Advantage

Many times, the best way to deliver a truly competitive solution is to leverage the products, skills, and resources of proven partners. Building on innovative Intel technology, UNICOM Engineering's design, integration, logistics and support expertise helps customers streamline software application deployment and shorten time to revenue. Our strong foundation of engineering expertise, process-driven manufacturing, technology partner relationships, and an unrelenting commitment to quality has made UNICOM Engineering one of the most trusted deployment partners in the industry.



R750-IR (Immersion Ready)

technical specifications



R750-IR Rear View

Form Factor

2U rack server

Dimensions

- Height 86.8 mm (3.41 inches)
- Width 482 mm (18.97 inches)
- Depth 758.3 mm (29.85 inches)

Processor

Up to two 3rd Generation Intel Xeon
 Scalable processors, with up to 40 cores
 per processor

Memory

- 32 DDR4 DIMM slots, supports RDIMM
 2 TB max or LRDIMM 8 TB max, speeds up to 3200 MT/s
- Up to 16 Intel Persistent Memory 200 series (BPS) slots, 8 TB max
- Supports registered ECC DDR4 DIMMs only

Storage Controllers

- Internal controllers: PERC H745, HBA355I, S150, H345, H755, H755N
- Boot Optimized Storage Subsystem (BOSS-S2): HW RAID 2 x M.2 SSDs 240 GB or 480 GB
- External PERC (RAID): PERC H840, HBA355E

Drive Bays

Front Bays:

- Up to 8 x 2.5-inch SSD max 122.88 TB
- Up to 16 x 2.5-inch SSD max 245.76 TB
- Up to 24 x 2.5-inch SSD max 368.84 TB Rear Bays:
- Up to 2 x 2.5-inch SSD max 30.72 TB
- Up to 4 x 2.5-inch SSD max 61.44 TB

Power Supplies

1400 W Platinum AC/240 HVDC

Cooling

Optimized for Immersion Cooling Systems

Fans

Optimized for Immersion Cooling Systems

Embedded Management

- iDRAC9
- iDRAC Service Module
- iDRAC Direct
- Quick Sync 2 wireless module

Embedded NIC

2 x 1 GbE LOM riser

Networking Options

■ 1 x OCP 3.0 (x8 PCle lanes)

GPU Options

 Up to two double-width 300 W, or four single-width 150 W, or six single-width 75 W accelerators

Ports

Front Ports:

- 1 x Dedicated iDRAC Direct micro-USB
- 1 x USB 2.0
- 1 x VGA

Rear Ports:

- 1 x USB 2.0
- 1 x Serial (optional)
- 1 x USB 3.0
- 2 x RJ-45
- 1 x VGA

Internal Ports

■ 1 x USB 3.0

PCIe

 Up to 8 x PCle Gen4 slots (up to 6 x16) with support for SNAP I/O modules

Operating System and Hypervisors

- Canonical Ubuntu Server LTS
- Citrix Hypervisor
- Microsoft Windows Server with Hyper-V
- Red Hat Enterprise Linux
- SUSE Linux Enterprise Server
- VMware ESXi

Note: These specifications should be viewed as preliminary and final specifications may vary.

Support and Maintenance Services

UNICOM Engineering offers a variety of support and maintenance service programs to ensure high availability, rapid response, effective troubleshooting, fast parts replacement and 24-hour support.

Please visit www.unicomengineering.com/supportservices for more information.



sales@unicomengineering.com





unicomengineering.com



+1 800.977.1010



twitter.com/UNICOMEng



linkedin.com/company/unicomengineering